

526,667

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau





(43) International Publication Date  
18 March 2004 (18.03.2004)

PCT

(10) International Publication Number  
**WO 2004/023182 A1**

- (51) International Patent Classification<sup>7</sup>: **G02B 6/22**, H01S 3/30
- (21) International Application Number: **PCT/FI2003/000646**
- (22) International Filing Date:  
4 September 2003 (04.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
20021580 4 September 2002 (04.09.2002) FI
- (71) Applicant (for all designated States except US): **LIEKKI OY [FI/FI]**; Sorronrinne 9, FIN-08500 Lohja AS (FI).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **TAMMELA, Simo [FI/FI]**; Visamäki 3 E 30, FIN-02130 Espoo (FI).
- (74) Agent: **TAMPEREEN PATENTTITOIMISTO OY**; Hermiankatu 12 B, FIN-33720 Tampere (FI).
- (81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: METHOD AND DEVICE FOR SPECTRAL FILTERING-

(57) **Abstract:** The invention refers to a method and a device in optical fiber based spectral filtering, where a length of an optical fiber (40) comprising at least a core region (CR) surrounded by a cladding region (CL) is coiled over its length in whole or in part to subject the fiber to longitudinal curvature in order to affect the optical transmission properties of the fiber. According to the invention the fiber (50) is arranged to have radially asymmetric refractive index distribution (R) and in addition to coiling the fiber lengthwise, the fiber is over its length in whole or in part also twisted around its longitudinal axis. The invention can be used to significantly improve the performance of fiber based filtering devices.

WO 2004/023182 A1